

R & D STATUS REPORT NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY (NORDA)

ARPA Order No. 4152,

Contract No. N00014-85-C-0793

Amendment 15

Contractor:

Principal Investigator:

Sierra Geophysics, Inc. 15446 Bell-Red Road Suite 400 Redmond, Washington 98052

Dr. George R. Mellman Vice President

(206) 881-8833

Dr. Marilee Henry Sr. Staff Geophysicist

Effective Date of Contract

August 13, 1985

Title of Work:

MSS Evaluation

Expiration Date:

August 13, 1986

Date of Report:

May 13, 1986

Date Due:

GG70

May 13, 1986

Feb 13, 1986 - May 13, 1986

Contract Period Covered By Report:

Sponsored by Defense Advanced Research Projects Agency (DoD)

The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Defense Advanced Research Projects Agency or the U.S. Government.

REPORT DOCUMENTATION PAGE								
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS						
23. SECURITY CLASSIFICATION AUTHORITY DARPA/TIO		3. DISTRIBUTION/AVAILABILITY OF REPORT						
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		Approved for Public Release Distribution Unlimited						
4. PERFORMING ORGANIZATION REPORT NUMBER(S) R&D Status Report/Period Covered: 86 02 13 to 86 05 13		5. MONITORING ORGANIZATION REPORT NUMBER(S)						
63. NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL (If applicable) 4R088	7a. NAME OF MONITORING ORGANIZATION Defense Advanced Research Projects Agency						
Sierra Geophysics, Inc. 4R088 GC. ADDRESS (City. State and ZIP Code) 15446 Bel-Red Road, Suite 400 Redmond, WA 98052		7b. ADDRESS (City, State and ZIP Code) 1400 Wilson Boulevard Arlington, VA 22209-2308						
84. NAME OF FUNDING/SPONSORING ORGANIZATION Naval Ocean Research &	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER						
Development Act. (NORDA) 8c. ADDRESS (City, State and ZIP Code)	N00014	N00014-85-C-0793						
Department of the Navy 800 N. Quincy Street Arlington, VA 22217-5000 11. TITLE (Include Security Classification) R&D Status Report (U)	PROGRAM ELEMENT NO.	PROJECT NO. ARPA Ord No. 4152 Amend.15		WORK UNIT NO.				
Dr. George R. Mellman; Dr	. Marilee Hen	ıry						
Quarterly R&D Statusnow86 (14. DATE OF REPOR		15. PAG	SE COUNT			
16. SUPPLEMENTARY NOTATION								
17. COSATI CODES	18. SUBJECT TERMS (C)	ontinue on reverse if ne	ecessary and identi	ify by block nur	m ber)			
FIELD GROUP SUB. GR.	18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) N/A							
19. ABSTRACT (Continue on reverse if necessary and identify by block number) N/A Accession For NTIS GRA&I DTIC TAB Unannounced Justification By Distribution/ Availability Codes Avail and/or Dist Special A-/					d/or			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT N/A UNCLASSIFIED/UNLIMITED SAME AS RPT. DTIC USERS		21. ABSTRACT SECURITY CLASSIFIDATION N/A						
J.A. Ballard, NORDA Code 340		22b. TELEPHONE NUMBER 22c. OFFICE SYMBOL (601) 688-4599 N68462						

A. <u>DESCRIPTION OF PROGRESS</u>

Current project status on a task by task basis is as follows:

TASKS 1 & 2:

1) Identify events detected and phases observed in MSS data:

All events visible on the unfiltered Gould and Teledyne MSS recordings have been identified for the short period channels SZ, SB, and SE, as discussed previously. Recently, high-pass filtering of continuous MSS short-period data obtained during the Bottom Processing Package (BPP) phase, recorded simultaneously on the vertical and hydrophone channels, has enabled detection of ~ 30 small magnitude events not visible in the unfiltered data. Currently this data set is being analyzed for comparison of down-hole and hydrophone waveforms, S/N values, and relative detection thresholds.

2) Cataloguing of pertinent MSS information and preliminary analyses:

Compilation of MSS information is currently being done. Problems encountered during data analysis have been listed in the 1985 report, as well as preliminary analyses by these authors and references of work done by others.

3) Comparison of MSS and OBS data and site characteristics:

As discussed in last status report, the S/N, observed phases, noise levels, and implied detection thresholds have been measured and compared for simultaneously recorded earthquake and noise data for the MSS and OBSes at the South Pacific site. MSS site m_h bias calibrated to ISC and

AFTAC magnitudes have been completed. Values of t* and Q from various phases observed in MSS data have been Signal enhancement and detection threshold estimated. improvement using an optimal band-pass filter and a simple polarization filter for regional and teleseismic events on MSS and OBSes have been examined. Since orientations for several OBSes have recently been determined, application of a true polarization filter on these data are now possible and will Currently, other signal enhancement attempted. techniques (such as stacking of water layer multiples) are being investigated for obtaining the best realistic detection thresholds on these instruments. Realization of this task will involve the use of various synthetic modeling techniques.

Sub-tasks not yet started include measurement of stability of phases across OBS array, calibration of MSS and OBS regional event magnitudes to P_n codas, and separation of near-source from near-receiver propagation effects.

TASK 3: SYSTEMS/SITES COMPARISON:

- 1) Analysis of the Wake Island hydrophone array data has begun for the period of time corresponding to the MSS South Pacific site recording period. Continuous Wake data are not available, only time windows surrounding expected or observed events (a total of \sim 77 "events"). The identification of P, P_n, S_n, and T phases, S/N measurements on spectra and time domain data, and noise levels are currently being compiled.
- 2) Two tapes of OSS borehole seismometer data (Kamchatka 1982 site) have been received from Hawaii and are currently being analyzed for noise level, S/N, and detection level comparisons with MSS, OBS, and hydrophone data.

TASK 4: SNAP-D SYSTEMS EVALUATION:

Work for this task will be initiated upon completion of the above mentioned analyses for MSS-83 and OSS-82 borehole data, OBS data, and Wake Island and MSS-83 hydrophone data.

B. SUMMARY OF PRELIMINARY FINDINGS SINCE LAST STATUS REPORT:

The hi-pass filtered continuous short-period MSS BPP data 1) revealed ~ 30 regional events having S/N << 1 in the original data. These events, recorded simultaneously on the vertical, horizontal, and hydrophone channels, had previously gone undetected in the unfiltered data. Individual events were hi-passed at 4.0, 6.0, and 11.0 Hz to find optimal S/N. The high-pass filter at 6.0 Hz was found to be optimal in most cases, though the hydrophone channel occasionally showed larger S/N on the data high-passed at 11 Hz. At this time, a direct comparison of S/N between the borehole and hydrophone channels has not been taken, as we do not possess the MSS hydrophone instrument response function, and it is unclear, since these are small magnitude events, whether time shifts are present between these channels. In general, the vertical borehole channel appears to show Pn onset more clearly than the hydrophone channel, whereas conversely, the hydrophone channel consistently shows higher amplitude water multiples, and occasionally larger P_n coda amplitudes compared to the borehole channels. Magnitudes measured on the vertical HP 6 Hz data for seven of these events with the best S/N ranged from 2.4 to 3.1 m_h at apparent distances of 7.3 to 8.9 degrees. When corrected to $S/N \sim 1$ and a reference distance of 10 degrees, the implied average detection threshold obtained was ~ 2.6 m_h.

2) In an attempt to verify the distance corrections derived for the MSS site for shallow regional events originating in the Tonga-Kermadec source region from MSS data, 32 events of a similar nature recorded on the OBSes during a different time were calibrated the same global to Unfortunately, these data were found to range over only ~ 1 degree of distance and displayed a very high average a magnitude bias of ~ 1.5 m.u. This large scatter in observed OBS versus published m_h 's may be due to the vaguaries of sediment response given the presumed unusual mode of Pn propagation. In comparison, MSS m_h 's calibrated to this global array resulted in an average delta $m_h^{} < 1$ m.u. over ~ 4 degrees of distance, and displayed an obvious trend with distance.

The detection threshold implied for this group of events recorded on the OBSes in trigger mode calibrated to the global array was $\sim 3.9~\text{m}_{\text{b}}$ on band-passed data at the reference distance of 10 degrees. Comparatively, the MSS detection threshold obtained for a different group of 14 shallow regional events was $\sim 3.5~\text{m}_{\text{b}}$ on band-passed data.

3) Preliminary analyses of a total of 77 recording windows of Wake Island hydrophone data have resulted in detections of 32 P and 22 P phases. (S_n and T phases have also been detected but have not yet been completely tabulated.) These events cover distances of ~ 20 to 70 degrees. Band-pass filtering improved S/N for both P and P_n phases, regional and teleseismic, with apparent optimal band-passes of 0.5 to 2.0 Hz for P, and 1.0 to 8.5 Hz for P_n phases. The average P phase delta m_h as calibrated to ISC magnitudes was ~ 0.5 m.u. (observed Wake magnitudes are high). (This in part may be due to imprecise knowledge of the instrument and telemetering cable responses.) No trends in magnitude bias distance or azimuth are evident. The detection thresholds implied for Wake Hydrophone P phases measured on

the filtered data are $\sim 5.0~\text{m}_\text{b}$ at 40 degrees and 5.3 m $_\text{b}$ at 60 degrees at a reference depth of 60 km and $S/N \sim 1$. The results obtained previously for the MSS teleseismic data were ~ 5.0 to 5.3 m_h for distances ranging from 40 to 80 degrees at a reference depth of 60 km. It therefore appears that for a single station, the Wake hydrophones and the MSS borehole instrument are nearly identical in their teleseismic P phase detection capabilities. Application of other enhancement techniques such as beam-forming and are water-multiple stacking expected to improve the hydrophone capabilities further.

The preliminary detection threshold obtained for the P_n phase on the band-pass-filtered Wake data was $\sim 4.4~m_b$ at 20 degrees distance range and $\sim 60~km$ depth, using distance corrections from the standard tables. Since no events in this study occurred at less than $\sim 20~degrees$ from the Wake array, a direct comparison of the detection threshold at regional distances to that of MSS is not obtainable. The MSS recorded only 2 events at 20 to 22 degrees distance, and using the standard tables for distance corrections for a reference depth of 60 km, a detection threshold of $\sim 4.6~m_b$ was obtained using S/N values from unfiltered data. Though sparse, these results concur with those of the teleseismic P phases in implying that the single station MSS and Wake hydrophone first arrival detection capabilities are very comparable for distances of 20 to 60 degrees.

C. SUMMARY OF NEEDED DATA OR OTHER INFORMATION

 Miscellaneous gain correction and instrument response functions are needed for Wake Hydrophone and OSS data.
 This will be arranged with U. of Hawaii personnel.

- 2) Any additional time periods needed for the AFTAC catalogue will be requested through Al Ballard in the near future.
- 3) The MSS hydrophone channel instrument response is needed. Problems also appear to exist with the MSS borehole instrument phase response. Inquiries have been made to Scripps Institution of Oceanography personnel, and will also be made to Gould.

D. PROPERTY & EQUIPMENT ACQUIRED

None

E. PERSONNEL CHANGES

None

F. TRAVEL

None

G. PLANS FOR NEXT REPORTING PERIOD

- 1) Complete observational analyses of Wake Island hydrophone data, including application of beam-forming and water-multiple-stacking signal enhancement techniques.
- 2) Complete observational analyses and signal enhancement studies on OSS data.
- 3) Design multiple-stacking filter for MSS, Wake hydrophone and OBS data.

4) Application of a polarization filter to OBSes with known orientations, and to OSS data where applicable.

H. RESEARCH TASKS FAILED OR TERMINATED

None

I. FISCAL STATEMENT

Of the total funds of \$188,040 authorized for 12 months, approximately 80% of the work has been completed.

J. COST DATA

Cumulative Cost Data as of April 30, 1986:

Labor Elements	Planned Amount (\$)	<u>Actual</u> <u>Amount (\$)</u>
Scientist Technical Support	\$ 30,528	\$ 39,906
Total Labor	30,528	39,906
Other Expenses		
Materia!	-0-	208
Travel	3,240	497
Computer	12,600	12,289
Total Other Expenses	\$ 15,840	\$ 12,994
Overhead	\$ 36,573	\$ 52,445
<u>G & A</u>	\$ 21,316	\$ 32,949
<u>Fee</u>	\$ 8,566	<u>\$ 11,365</u>
GRAND TOTAL	\$112,823	\$149,659

K. PLANNING ESTIMATES

Revised Planning Estimate as of April 30, 1986 (Cumulative Costs)

Reporting Period								
	<u>1st*</u>	<u>2nd</u> *	<u>3rd</u> *	4th	5th			
Planned Percentage of Technical Completion	20%	40%	60%	80%	100%			
Labor Elements	\$	\$	\$	\$	\$			
Scientist Technical Support	10,941	25,876	39,906	40,705	50,881			
Total Labor	10,941	25,876	39,906	40,705	50,881			
Other Expenses								
Material	42	208	208	-0-	-0-			
Travel	-0-	497	497	4,320	5,400			
Computer	1,762	5,844	12,289	16,800	21,000			
Total Other Expenses	1,804	6,549	12,994	21,120	26,400			
Overhead	11,606	29,124	52,445	48,764	60,955			
<u>G & A</u>	5,333	13,244	32,949	28,421	35,527			
Fee	2,439	6,146	11,365	11,421	14,277			
GRAND TOTAL	\$32,123	\$80,939	\$149,659	\$150,431	\$188,040			
(*Actual)								